

T S1/5/1

1/5/1

DIALOG(R)File 347:JAPIO

(c) 2003 JPO &amp; JAPIO. All rts. reserv.

04445169 \*\*Image available\*\*

PHOTOSENSITIVE DRUM, PROCESS CARTRIDGE, IMAGE FORMING DEVICE AND IMAGE FORMING SYSTEM

PUB. NO.: 06-089069 [JP 6089069 A]

PUBLISHED: March 29, 1994 (19940329)

INVENTOR(s): NISHIHATA ATSUSHI

TSUDA TADAYUKI

MIZUTANI MORIKAZU

SEKINE KAZUMI

WATANABE KAZUFUMI

KOBAYASHI KAZUNORI

NODA SHINYA

SASAKO ETSUICHI

SHIMIZU YASUSHI

IKEMOTO ISAO

APPLICANT(s): CANON INC [000100] (A Japanese Company or Corporation), JP (Japan)

APPL. NO.: 05-017851 [JP 9317851]

FILED: January 11, 1993 (19930111)

INTL CLASS: [5] G03G-021/00; F16C-013/00; G03G-015/00; G03G-015/09

JAPIO CLASS: 29.4 (PRECISION INSTRUMENTS -- Business Machines); 22.1 (MACHINERY -- Machine Elements)

JAPIO KEYWORD: R002 (LASERS); R124 (CHEMISTRY -- Epoxy Resins)

JOURNAL: Section: P, Section No. 1763, Vol. 18, No. 349, Pg. 129, June 30, 1994 (19940630)

## ABSTRACT

PURPOSE: To obtain a stable structure of photosensitive drum having a large area when the photosensitive drum is preliminarily mounted on a mount, by assembling gears in a manner that the first helical gear in the outer side has a larger diameter than the second helical gear in the inner side.

CONSTITUTION: The photosensitive drum 9 is produced by coating a cylindrical aluminum drum base body (cylinder) 9a with an organic photosensitive layer by dipping method or the like. The one end of the aluminum drum base body 9a has a flange gear 9c and a gear 9i fixed by caulking. The flange gear 9c and the gear 9i are attached adjacent to each other on the end of the drum base body 9a in a manner that the flange gear 9c in the outer side has a large diameter than the gear 9i in the inner side. Thereby, when this drum 9 is left to stand on a mounting space 60 of a working desk or floor for assembling or maintenance to exchange parts of the device, stability of the drum is improved.

?